# 2024 FORD RANGER® RAPTOR® TECHNICAL SPECIFICATIONS



| Construction            | Body-on-frame                                                                       |
|-------------------------|-------------------------------------------------------------------------------------|
| Body styles             | SuperCrew®                                                                          |
| Final assembly location | Michigan Assembly Plant, Wayne, Michigan                                            |
|                         |                                                                                     |
| ENGINE                  |                                                                                     |
|                         | 3.0-liter EcoBoost® V6                                                              |
| Configuration           | Twin-turbocharged and intercooled V6, compacted graphite iron block, aluminum heads |
| Valvetrain              | DOHC, four valves per cylinder, twin independent variable camshaft timing           |
| Ignition                | Coil on plug                                                                        |
| Bore x stroke           | 3.36 x 3.38 inches (85.4 mm x 86.0 mm)                                              |
| Displacement            | 180.0 cubic inches (2,949 cubic centimeters)                                        |
| Compression ratio       | 10.5:1                                                                              |
| Recommended fuel        | 91 octane                                                                           |
| Fuel capacity           | 20.3 gallons                                                                        |
| Fuel delivery           | Port fuel and direct injection                                                      |
| Power                   | 405 horsepower                                                                      |

### DRIVETRAIN

Layout

Torque

BODY

Standard - 4x4 front locking differential, rear drive with electronic locking differential

### TRANSMISSION

Standard

10-speed SelectShift® automatic

430 lb.-ft.



# **GEAR RATIOS**

| First                        | 4.714:1                                                                                                                           |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Second                       | 2.997:1                                                                                                                           |
| Third                        | 2.149:1                                                                                                                           |
| Fourth                       | 1.769:1                                                                                                                           |
| Fifth                        | 1.521:1                                                                                                                           |
| Sixth                        | 1.275:1                                                                                                                           |
| Seventh                      | 13                                                                                                                                |
| Eighth                       | 0.853:1                                                                                                                           |
| Ninth                        | 0.689:1                                                                                                                           |
| Tenth                        | 0.636:1                                                                                                                           |
| Reverse                      | -4.885:1                                                                                                                          |
| Final drive front axle ratio | 4.70:1                                                                                                                            |
| Final drive rear axle ratio  | 3.73:1                                                                                                                            |
|                              |                                                                                                                                   |
| TRANSFER CASE                |                                                                                                                                   |
| Туре                         | 2-speed transfer case with 4H, 4L and 4A mode for                                                                                 |
| Maximum crawl ratio          | 67.88:1                                                                                                                           |
| SUSPENSION                   |                                                                                                                                   |
| Front                        | Forged aluminum double A-arm suspension with 2.5-inch Fox® Live Valve shocks                                                      |
| Rear (standard)              | Watts-link rear suspension with trailing arms and Fox® Live Valve shocks                                                          |
| (Standard)                   | watts tink real suspension with training arms and rox. Eive valve shocks                                                          |
| STEERING                     |                                                                                                                                   |
| Туре                         | Electric power-assisted, rack-and-pinion                                                                                          |
| Turning circle, curb-to-curb | 43.3 feet                                                                                                                         |
|                              |                                                                                                                                   |
| BRAKES                       |                                                                                                                                   |
| Туре                         | Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac® electronic stability control |
| Front                        | 12.24- x 1.33-inch disc, 2.0-inch twin piston caliper, non-asbestos organic pads                                                  |
| Rear                         | 12.12- x 0.94-inch disc, 2.12-inch single piston caliper, non-asbestos organic pads                                               |
|                              |                                                                                                                                   |
| WHEELS AND TIRES             |                                                                                                                                   |

# WheelsTiresStandard17-inch Gray-Painted Aluminum Wheel33-inch All-Terrain LT 285/70R17Optional17-inch Gray-Painted Beadlock Capable Wheel33-inch All-Terrain LT 285/70R17



### DIMENSIONS (ALL MEASUREMENTS IN INCHES UNLESS OTHERWISE NOTED)

### EXTERIOR

|                                  | SuperCrew 4x4 |
|----------------------------------|---------------|
| Wheelbase                        | 128.7         |
| Overall length                   | 210.9         |
| Overall width                    | 86.7          |
| Width with mirrors folded        | 79.0          |
| Width excluding mirrors          | 79.8          |
| Overall height                   | 75.9          |
| Track, front                     | 67.3          |
| Track, rear                      | 67.3          |
| Approach Angle                   | 33°           |
| Departure Angle                  | 26.4°         |
| Ramp Breakover Angle             | 24.20         |
| Minimum Running Ground Clearance | 10.7          |
| Front Overhang                   | 33.9          |
| RearOverhang                     | 48.2          |
| Curb weight (lbs)                | 5,325         |
|                                  |               |
| INTERIOR                         |               |
| Seating capacity                 | Five          |
| Front headroom                   | 41.0          |
| Front legroom, maximum           | 43.7          |
| Front shoulder room              | 57.1          |
| Front hip room                   | 55.9          |
| Rearheadroom                     | 38.3          |
| Rearlegroom                      | 38.3          |
| Rear shoulder room               | 57.1          |

Rear hip room54.1Passenger volume (cu. ft.)98.3AirbagsDual-stage driver and right front passenger, front seat side and Safety Canopy® System

### CAPACITIES

**CARGO BED AREA** 

|                                   | SuperCrew 4x4 |
|-----------------------------------|---------------|
| Lift in height (inches)           | 36.1          |
| Length at floor (inches)          | 59.6          |
| Width at wheelhouse (inches)      | 48.2          |
| Maximum width inside box (inches) | 62.4          |
| Cargo capacity (cu. ft.)          | 43.5          |
| Maximum payload (lbs.)            | 1,411         |
| GVWR (lbs.)                       | 6,790         |
| Maximum towing (lbs.)             | 5,510         |
| GCWR (lbs.)                       | 11,465        |



## TECHNOLOGY

| Ford CoPilot-360 ™ features* | Lane Centering, Auto High Beams, BLIS® (Blind Spot Information System) with Cross-Traffic Alert and Trailer Coverage,<br>Pre-Collision Assist with Automatic Emergency Braking (AEB), Rearview Camera, Intersection Assist, Active Park Assist<br>2.0, Evasive Steering Assist, Evasive Steering Assist, Reverse Braking Assist, Intersection Assist, Speed Sign Recognition,<br>Post Collision Braking, Intelligent Speed Limiter, Forward Collision Warning, Reverse Brake Assist                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Off-Road*                    | Terrain Management System™, Trail Control™, Drive Modes, Off-road screen with front camera view                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| In-Cabin*                    | SYNC®, SYNC® 4A, Apple CarPlay™ compatibility, Android Auto™ compatibility, navigation system, FordPass® Connect™<br>with 4G LTE Wi-Fi, SiriusXM® satellite/HD Radio™, B&O Sound System by Bang & Olufsen, standard 8-inch digital<br>instrument cluster, available 12.4-inch digital instrument cluster, 360-Degree Camera                                                                                                                                                                                                                 |
| General*                     | Pro Trailer Backup Assist, integrated trailer brake controller, Zone Lighting, Lane Centering, Wireless phone charging,<br>400W inverter, USB A and USB C charging, Trailer Navigation, Trailer Reverse Guidance, Adaptive Cruise Control with<br>Stop-and-Go, Forward and Reverse Sensing Systems, Intelligent Access with push-button start, Remote Start System,<br>LED headlamps, LED taillamps, SecuriCode™ keyless entry keypad, wiper-activated headlamps, windshield wiper<br>de-icer, rain-sensing wipers and trailer sway control |

For editorial use only. Information correct at time of publication.

\*Standard and available features based on model and option packages. Check media ford.com for updates.

